

CAMERA SPECIFICATIONS

Vendor Model #/Style #	63054	63055	63056
Camera Model	Primos Proof Cam 01 HD -- 10MP Game Camera	Primos Proof Cam 02 HD -- 12MP Game Camera	Primos Proof Cam 03 HD -- 12MP Game Camera
Shooting modes	Photos, Videos, HD Time Lapse, Time Lapse with PIR Day & Night Photos	Photos, Videos, HD Time Lapse, Time Lapse with PIR Day & Night Photos	Photos, Videos, HD Time Lapse, Time Lapse with PIR Day & Night Photos
Image sensor	3.0 MP Color CMOS	3.0 MP Color CMOS	3.0 MP Color CMOS
Photo resolution settings	Large(3648x2736), Small(2048x1536)	Large(4000x3000), Small(1920x1440)	Large(4000x3000), Small(1920x1440)
Photo burst settings	1, 2, 3, 4, 5	1, 2, 3, 4, 5	1, 2, 3, 4, 5
Video resolution settings	1280x720HD(30fps), 320x240(30fps)	1280x720HD(30fps), 320x240(30fps)	1280x720HD(30fps), 320x240(30fps)
Video length settings	5s, 10s, 15s, 20s, 30s, 60s	5s, 10s, 15s, 20s, 30s, 60s	5s, 10s, 15s, 20s, 30s, 60s
Sound Recording	Video Mode Records Audio	Video Mode Records Audio	Video Mode Records Audio
Time Lapse Video Resolution	1280x960 (10fps)	1280x960 (10fps)	1280x960 (10fps)
Time Lapse interval settings	1m, 2m, 5m, 10m, 30m, 60m	1m, 2m, 5m, 10m, 30m, 60m	1m, 2m, 5m, 10m, 30m, 60m
Lens	7.5mm f/3.0	7.5mm f/3.0	7.5mm f/3.0
Field of View	45°	45°	45°
Zoom	fixed	fixed	fixed
ISO sensitivity	100	100	100
Infrared Illumination	36 High-Output IR Emitters;Up to 70ft	48 High-Output IR Emitters;Up to 100ft	60 High-Output IR Emitters;Up to 80ft
PIR Sensor	Multi Zone	Multi Zone	Multi Zone
PIR Sensitivity	Auto, 45°	Auto, 45°	Auto, 45°

Vendor Model #/Style #	63054	63055	63056
Trigger Time	0.7 Second	0.4 Second	0.4 Second
Removable Memory	up to 32 GB SD Card	up to 32 GB SD Card	up to 32 GB SD Card
System requirements (Windows)	Windows 2000, XP, Vista, Win7 or Win 8; USB port	Windows 2000, XP, Vista, Win7 or Win 8; USB port	Windows 2000, XP, Vista, Win7 or Win 8; USB port
System requirements (Mac)	Mac OS X 10.10 or later; USB port	Mac OS X 10.3 or later; USB port	Mac OS X 10.3 or later; USB port
Display	1.1" Character LCD	1.1" Character LCD	1.1" Character LCD
User Interface	Sliding Switches	Sliding Switches	Sliding Switches
Image Stamp	Burst Count, Moon Phase, Temperature, 12 Hour US Time (AM/PM), Date, Day of the Week	Burst Count, Moon Phase, Temperature, 12 Hour US Time (AM/PM), Date, Day of the Week	Burst Count, Moon Phase, Temperature, 12 Hour US Time (AM/PM), Date, Day of the Week
Memory	SD Memory up to 32 GB card size (not included)	SD Memory up to 32 GB card size (not included)	SD Memory up to 32 GB card size. (not included)
Mounting	Adjustable Webbing Strap with Buckle	Adjustable Webbing Strap with Buckle	Adjustable Webbing Strap with Buckle
Power requirements	8xAA Batteries (not included);12V DC in	8xAA Batteries (not included);12V DC in	8xAA Batteries (not included);12V DC in
Standby Current	< 0.25 mA (<mAh/Day)	< 0.25 mA (<mAh/Day)	< 0.25 mA (<mAh/Day)
Power Consumption (12V Power in)	90mA (+960mA with IR)	90mA (+960mA with IR)	90mA (+1100mA with IR)
Power Consumption	"SD Card Slot USB Jack 12V DC Jack"	"SD Card Slot USB Jack 12V DC Jack"	"SD Card Slot USB Jack 12V DC Jack"
Product height (in.)	2.5	2.5	2.5
Product width (in.)	4.25	4.25	4.25
Product length (in.)	5.25	5.25	5.25
Product weight (lb)	Approx 1.5lbs	Approx 1.5lbs	Approx 1.5lbs
Operation / Storage Temps	"Storage: -10°F to 140°F Operation: 20°F to 120°F"	"Storage: -10°F to 140°F Operation: 20°F to 120°F"	"Storage: -10°F to 140°F Operation: 20°F to 120°F"
Security Authentication	FCC, CE, RoHS	FCC, CE, RoHS	FCC, CE, RoHS